NHS England MPK Orion3 Package (ORION3NHSP)

Extended warranty of 5 years on the Orion3 and standard 3 years warranty on the Esprit and Epirus Feet.
Due to data protection and the method of returning these forms please do not include any additional information other than that requested.

Patient Details

Bleuteq Ref:							
Weight	kg	Foot Size	cm	☐ Left	☐ Right	☐ Bilateral	
Knee Disarticulation		Transfemoral		Hip Disartic/Hemi			
Activity Level		KC to Ground	cm				

For sizes 25-28 please choose between N (Narrow) and W (Wide) fitting.

Users at Level 2 and 4 activity who would benefit from this foot will require softer or stiffer springs as appropriate for the individual.
Spring set recommendations are for trans-tibial users. For trans-femoral we suggest selecting a spring set one level lower.

Activity	User Weight								
	44-52 / 100-115	53-59 / 116-130	60-68 / 131-150	69-77 / 151-170	78-88 / 171-195	89-100 / 196-220	101-116 / 221-255	117-125 / 256-275	kg / lbs
3	1	2	3	4	5	6	7	8	Spring set

Shipping Details

Order No.		Company	
Address			
Prosthetist			
Contact Tel No.		Email	

Socket Adapter (one of):

☐ 4ST6 (3 prong Lamination adapter with female pyramid)



☐ 4S35 (3 prong Lamination for minimum M36 build)



Proximal Knee Adapter (one of):

☐ 239017 Rotating pyramid with shift (for use with 4ST6)



☐ 239089 Non – Rotating pyramid with shift (for use with 4ST6)



☐ 239092 M36 Threaded Adapter (for use with 4S35)



Orion3 Knee (with charger):

☑





Suitable for outdoor use

Blatchford

Distal Tube/Adapter

Please select one of the combinations below:

	Qty.	Part No.	Description		Qty.	Part No.	Description	Build Height	Product Weight	Maximum Patient Weight
☐	2x	AK30M1*	Tube clamp adaptor pyramid female 30mm		1x	330120	30mm carbon fibre pylon	Max. build height 250mm	100g	Activity level 1-4 100kg
☐	1x	AK30M1*	Tube clamp adaptor pyramid female 30mm		1x	409053	30mm female pyramid pylon adaptor	Min. build height 60mm Max build height 90mm	97g	Activity level 1-3 125kg Activity level 4 100kg
☐	2x	AK30M1*	Tube clamp adaptor pyramid female 30mm		1x	903220/400	30mm aluminum pylon	Max. build height 400mm	285g	Activity level 1-3 125kg Activity level 4 100kg

*Product Weight: 92g per AK30M1 module. Maximum Patient Weight: 150kg/Activity levels 1-3 & 145kg/Activity level 4. Build Height: 15mm (51mm overall) per AK30M1 module.

OR

(one of the following double adapters with rotation)

☐ 3T54 (34mm) ☐ 3T56 (53mm)

☐ 3T55 (42mm) ☐ 3T57 (66mm)



Select foot by placing a tick in the box. Enter the size requirements in the table below.

Foot (one of):

☐ Esprit

Suitable for submersion



Product Code: ES

☐ Epirus

Suitable for outdoor use



Product Code: EP

☐ Dark Tone Foot Shell

Product Code	Size	Side	Width*	Spring Set	Sandal Toe
ES	22	L	-	1	S

Narrow (N) and Wide (W) available for sizes 25-28 only.

Orion Knee Fairing

(if required)

☐ 561093



N.B. The weight limit on the complete prosthesis is determined by its lowest rated component.

Reset Form