NHS England MPK Orion3 VT or ER Package (ORION3NHSP4)

An Extended Life Package of 5 years covering both the Orion3 knee and the Echelon VT or ER foot

Due to data protection and the method of returning these forms please do not include any additional information other than that requested.

Patient Details

Bleuteq Ref:							
Weight	kg	Foot Size	cm	☐ Left	☐ Right	☐ Bilateral	
Knee Disarticulation		Transfemoral		Hip Disartic/Hemi			
Activity Level		KC to Ground	cm				

For sizes 25-28 please choose between N (Narrow) and W (Wide) fitting.

Activity Level 2 and 4* users who would benefit from this foot will require softer or stiffer springs as appropriate for the individual.

Spring set recommendations are for trans-tibial users. For trans-femoral we suggest selecting a spring set one level lower.

Activity	User Weight								
	44-52	53-59	60-68	69-77	78-88	89-100	101-116	117-125	kg
	100-115	116-130	131-150	151-170	171-195	196-220	221-255	256-275	lbs
3	1	2	3	4	5	6	7	8	Foot spring set
	•		••		•••		••••		◀ Axial shock spring rate indicated as shown
	1		2		3		4		◀ Axial spring

Shipping Details

Order No.		Company	
Address			
Prosthetist			
Contact Tel No.		Email	

Socket Adapter (one of):

☐ 4ST6 (3 prong Lamination adapter with female pyramid)



☐ 4S35 (3 prong Lamination for minimum M36 build)



Proximal Knee Adapter (one of):

☐ 239017 Rotating pyramid with shift (for use with 4ST6)



☐ 239089 Non – Rotating pyramid with shift (for use with 4ST6)



☐ 239092 M36 Threaded Adapter (for use with 4S35)



Orion3 Knee (with charger):

☑





Suitable for outdoor use

Blatchford

Distal Tube/Adapter

Please select one of the combinations below:

	Qty.	Part No.	Description		Qty.	Part No.	Description	Build Height	Product Weight	Maximum Patient Weight
☐	2x	AK30M1*	Tube clamp adaptor pyramid female 30mm		1x	330120	30mm carbon fibre pylon	Max. build height 250mm	100g	Activity level 1-4 100kg
☐	1x	AK30M1*	Tube clamp adaptor pyramid female 30mm		1x	409053	30mm female pyramid pylon adaptor	Min. build height 60mm Max build height 90mm	97g	Activity level 1-3 125kg Activity level 4 100kg
☐	2x	AK30M1*	Tube clamp adaptor pyramid female 30mm		1x	903220/400	30mm aluminum pylon	Max. build height 400mm	285g	Activity level 1-3 125kg Activity level 4 100kg

*Product Weight: 92g per AK30M1 module. Maximum Patient Weight: 150kg/Activity levels 1-3 & 145kg/Activity level 4. Build Height: 15mm (51mm overall) per AK30M1 module.

OR

(one of the following double adapters with rotation)



☐ 3T54 (34mm)
☐ 3T55 (42mm)
☐ 3T56 (53mm)
☐ 3T57 (66mm)

Foot:

☐ EchelonVT

Suitable for outdoor use

Product Code: ECVT



☐ Dark Tone Foot Shell

☐ EchelonER

Suitable for submersion

Product Code: ECER



Enter the size requirements in the table below. N.B. Axial Spring not required for EchelonER.

Product Code	Size	Side	Width*	Spring Set	Axial Spring	Sandal Toe
ECVT	22	L	-	1	1	S

Narrow (N) and Wide (W) available for sizes 25-28 only.

Orion Knee Fairing

(if required)

☐ 561093



N.B. The weight limit on the complete prosthesis is determined by its lowest rated component.

Reset Form